

4"

R95-VC



4"

R95-VC



Electric submersible pump R95 series is suitable for lifting clean water in wells, domestic, civil and industrial applications, including water supply, irrigation systems.

R95-VC series capacity range: 2m³/h ~ 5.5m³/h, max total head: 511m.

SIZE CHARTS

Model	A	B	C	D	E	Φmax
R95-VC-06	784	366	418			
R95-VC-09	864	386	478			
R95-VC-12	974	406	568			
R95-VC-16	1132	441	691			
R95-VC-20	1344	501	843			
R95-VC-24	1571	561	1010	G1 1/2"	95	100
R95-VC-28	1689	561	1128			
R95-VC-37	2006	601	1405			
R95-VC-50	2566	721	1845			
R95-VC-60	3012	841	2171			
R95-VC-70	3336	841	2495			



SELECTION CHARTS

Model 50Hz	Motor Power		Three Phase				Single Phase				Capacity												
			380V		220V		Q		Capacity														
			HP	kW	A	A	μF	VC	US.gpm	Capacity													
R95-VC-06	0.75	0.55	2	4.8	25	450	46	42	38	36	32	30	25	20	0	8.8	13.2	15.4	17.6	19.8	22	24.2	
R95-VC-09	1	0.75	2.5	6.3	35	450	63	58	55	50	48	40	36	29	0	2	3	3.5	4	4.5	5	5.5	
R95-VC-12	1.5	1.1	3.4	8.6	45	450	86	80	76	68	64	56	48	38	0	33	50	58	67	75	83	92	
R95-VC-16	2	1.5	4.4	10	55	450	115	105	101	90	85	75	64	51									
R95-VC-20	3	2.2	6.2	14	70	450	150	142	130	120	107	98	85	75									
R95-VC-24	4	3	8.3	19.5	80	450	175	170	152	148	138	120	100	88									
R95-VC-28	4	3	8.3	19.5	80	450	210	195	178	168	150	138	120	100									
R95-VC-37	5.5	4	10.3	27	120	450	268	255	230	210	190	168	138	105									
R95-VC-50	7.5	5.5	14	-	-	-	370	350	330	305	280	250	215	165									
R95-VC-60	10	7.5	18.5	-	-	-	438	420	378	348	330	288	240	180									
R95-VC-70	10	7.5	18.5	-	-	-	511	490	441	406	385	336	280	210									

